

FIREFIGHTING SUPPORT TANKER



TIMAK's Firefighting Support Tankers are designed for extended fire operations and backup support in urban areas.

With high-capacity pumps, water and foam tanks, and essential equipment, they supply frontline units and adapt to specific operational needs.

TECHNICAL SPECIFICATIONS



Standard Specifications

Chassis: 4x2, 6x2, 6x4, 8x2, 8x4	Front Irrigation:Pre-pressurized + rear free flow
Body: Modular structure	Lighting: Lightbar with siren + 2 fixed projectors
Water Tank: 6,000-18,000 L (stainless steel)	Hose Reel: 1 unit, manual unwinding / electric rewind (1" x 50 m hose with Jet/Fog pistol)
Foam Tank: 150-500 L (stainless steel)	Suction strainer, suction hoses, branchpipes, fire hoses, union wrenches, portable ladder
Pump Options: • TMK 1500 N – 1,500 L/min @ 10 bar (PTO) • TMK 3000 NH – 2,000 L/min @ 10 bar, 250 L/min @ 40 bar (PTO) • TMK 4000 N – 4,000 L/min @ 10 bar (PTO) • Foam mixing 3%–6% around the pump	
Monitors: • TMK 1200 – 1,200 L/min (manual) • TMK 2400 – 2,400 L/min (manual) • TMK 3000 – 3,000 L/min (manual)	



Optional Specifications

Telescopic projector	Additional firefighting or rescue equipment
Attachable first intervention hose reel	Rear locker configuration
Remote-controlled monitor	Extra storage lockers on demand



Contact Us for more information or a quotation.
info@timak.com